

# ZXL-TINY-LED

LED Hanging/Pendant . ZXLSeries



## Product Features

- 0.5" dia. suspension LED fixture with acrylic rod.
- ETL outdoor wet location listed. IP65 standard.
- Machined from solid billet 6061-T6 corrosion resistant aluminum.
- Modular components - field changeable LED module.
- Brushed acrylic hood provide even glow through out, and subtle lighting around the fixture.

## Specification

### Materials:

Body: Machined from billet 6061-T6 corrosion resistant aluminum with 304 stainless steel hardware. Available in 304/316 stainless steel or 360 brass upon request.  
Hood: Brushed acrylic rod.

**Wattage:** 1W HK LED.

**Light Source:** CRI 83. Available in CRI95 upon request. The chromaticity range is within a 3-step McAdam Ellipse. Standard CCT options are 2700K, 3000K, 4000K.

**Finish:** Polyester powder coat on all aluminum materials with RoHS compliant procedures. Anodized finish is available. Stainless steel and brass models are provided with brushed surface.

**Fixture Weight:** 1lb.

**Dimmability:** MLV or ELV.

**Mounting Method:** Mount cable on tree branches or beam using screw-mount-cable ties, or attach to a canopy plate/box for pendant application. Standard fixture comes with 5' 18/2 SJTW power cable.

**Voltage:** 12V AC/DC. Requires remote step down transformer.

## Ordering Guide

EXAMPLE: ZXL-TINY-LED - 1 - 12V - BK

SERIES	WATTAGE	VOLTAGE	CCT	FINISH
ZXL-TINY LED	1	12V	27 2700K 30 3000K 40 4000K	BK BLACK POWDER COAT BZ BRONZE POWDER COAT WT WHITE POWDER COAT ABK ANODIZED BLACK ACL ANODIZED CLEAR CC CUSTOM POWDER COAT NBR NATURAL BRASS NSS NATURAL STAINLESS STEEL

Remote Step Down Transformer (Optional).  
See "[Accessories](#)" link for detailed specification.

Model	Wattage(VA)	Primary Voltage(VAC)	Secondary Volt(VAC)	Dimming Method	Characters
TXM	20 40 60 100 150 300	120 277	12	MLV	Outdoor, Wall Mount, Compact
TXS	150 300 600	120	Multi-tap of 12, 13, 14, 15 VAC	MLV	Outdoor, Wall mount, Stainless Steel Case
IGT	50 100 300 600	120	12	MLV	in grade
TXE	60	120 230 277	12	ELV	Needs Enclosure, 6ft working distance

## Product Drawings

NOTE: Specification and dimensions subject to change without notice.

